

- Chrome coated or PC spot frame in white color
- 316 L Press forming chrome body
- Polycarbonate glass
- 316 L Stainless connectors
- Operates with alternate or direct current
- Underwater connector
- H07RNF rubber cable
- Plastic injection mounting box (optional)

P W Product & Power Options

Product Name	Light Color	Input Voltage (V)	Power (W)	Luminous Flux (lm)	Weight (kg)
AC5G18	WW-NW-CW	12-24V DC	21	2.100	1,2
AC5G18	WW-NW-CW	12-24V DC	32	3.200	1,2
AC5G18	WW-NW-CW	12-24V DC	46	4.800	1,2
AC5G18*	RGB	24V DC	26	-	1,2
AC5G18*	RGB	24V DC	36	-	1,2

Power and Lumen values provided are based off of a lensless product with cold white (CW) LED. It may vary according to the desired color.
* RGB products can be produced in 12-24 V DC and product values may vary

C Light Color Options

● WW: Warm White	3000K	● R: Red	625nm
● NW: Natural White	4000K	● G: Green	525nm
● CW: Cold White	6500K	● B: Blue	465nm
● RGB		● A: Amber	590nm

S System Options

- 01 Standart (ON/OFF)
- 02 PWM-DIM
- 03 Invert PWM-DIM

O Lens Options



XN: Extra Narrow Angle

N: Narrow Angle

M: Medium Angle

XW: Without lens

U Upper Piece Options



15: Chrome coated

16: White




Order Code

P . W . C . S . O . U



Product Diagrams

Polar Diagram



Conical Diagram

H (mt)	Ø (m)	E _{max} (lx)
3.0	7,52	97
2.5	6,26	140
2.0	5,01	218
1.5	3,76	388
1.0	2,51	873
0.5	1,25	3490

AC5G 18LED CW 120D 20W 12-24V DC IP68

Accessories



34600134: Mounting Box

Control System Options

Color Type	PWM	INV PWM	DMX	DALI	0-10V DC	TRIAC
WW-NW-CW	•	•		•	•	
R,G,B,A	•	•		•	•	
RGB	•	•				
RGBA/W						
RGB DMX			•			
WHITE DMX			•			

Product Code	Voltage (V DC)	Control Systems	Cable Core Quantity		
			Mono	RGB	RGB W/A
AC5G18	12	PWM	2x	4x	-
	12-24	ON/OFF	2x	-	-
	12-24	INV-PVM	3x	5x	-



Royal Seginus Hotel, Antalya