

- Min. 20 micron anodized aluminum extruded profile
- High efficient homogeneous light via plexiglas diffused cover
- Suitable for pendant mounting
- Different colors are applicable for the housing
- 1,5 m steel wire hangers are included
- The number of the hangers in the package may vary regarding the product size

P W Product & Power Options


Product Name	Light Color	Input Voltage (V)	Power (W)	Luminous Flux (lm)	Weight (kg)
BLZTria	WW-NW-CW	24V DC	55	4.125	4,2
BLZTria	WW-NW-CW	24V DC	80	6.000	4,2

*Power and Lumen values provided are based off of a cold white (CW) LED.

C Light Color Options

● WW: Warm White	3000K	● R: Red	625nm
● NW: Natural White	4000K	● G: Green	525nm
● CW: Cold White	6500K	● B: Blue	465nm
● RGB		● A: Amber	590nm

G Housing Color/Coating Options



01: Anodized RAL9005 RAL9016 29: Walnut 30: Dark Walnut 31: Oak 32: Light Walnut

Control System Options

Color Type	PWM	INV PWM	DMX	DALI	0-10V DC	TRIAC
WW-NW-CW	●			●	●	
R,G,B,A	●			●	●	
RGB	●					
RGBA/W						
RGB DMX						
WHITE DMX						



Order Code

P . W . C . G

