



- Aluminum body
- Fixed (unchanging) or changing color option
- Works silently, without the need for fan cooling
- Up to 200 mixed fiber optic strands
- **See size options in table FO package options*

P W Product & Power Options

Product Name	Light Color	Input Voltage (V)	Power (W)	Weight (kg)
IK7-V2	WW-NW-CW	220-240V AC	2	0,3
IK7-V2	WW-NW-CW	5V DC	2	0,3
IK7-V2	RGB	7,5V DC	6	0,3

C Light Color Options

● WW: Warm White	3000K	● R: Red	625nm
● NW: Natural White	4000K	● G: Green	525nm
● CW: Cold White	6500K	● B: Blue	465nm
		● A: Amber	590nm

UZ Lenght Options

0 (Only light source)	200cm
100cm	300cm
150cm	500cm

PK Package Options

50 Mixed Strand	150 Mixed Strand
75 Mixed Strand	200 Mixed Strand
100 Mixed Strand	

Fo Package Options

Fiber Optic Cable Type	50 Mixed strand (qty)	75 Mixed strand (qty)	100 Mixed strand (qty)	150 Mixed strand (qty)	200 Mixed strand (qty)
20	0	0	0	88	133
30	20	40	60	30	40
40	10	16	25	15	15
60	8	10	8	10	8
80	6	5	5	5	2
100	3	2	1	1	1
120	3	2	1	1	1

Control System Options

Color Type	PWM	INV PWM	DMX	DALI	0-10V DC	TRIAC
WW-NW-CW	•				•	
R,G,B,A	•				•	
RGB	•					
RGBA/W	•					
RGB DMX						
WHITE DMX						



Order Code

P . W . C . UZ . PK

